



MICHELIN®

WIDE BASE XZL™

The all-position wide base radial engineered to handle off-road punishment while maintaining a high level of traction and mobility.



MICHELIN

MICHELIN® WIDE BASE XZL™

The long-wearing all-terrain wide base radial optimized for traction and mileage.

Self-cleaning, open shoulder tread design features offset tread elements to enhance traction and flotation capabilities, allowing the XZL to aid in vehicle mobility.

Deep 27/32nds tread helps increase tread life.

Stable block design helps create a consistent footprint enabling the tread to wear evenly while delivering a smooth, quiet ride.

Full 9/32nds undertread, full-width steel belts, and elastic protector ply help provide extra casing protection against off-road hazards, lowering downtime.

Application-specific tread compounds help provide excellent chip resistance, extending tread and casing life.

Rectangular bead bundles – a Michelin exclusive – “strap” the tire to the wheel and are designed to provide easier mounting, excellent handling, increased vehicle stability, and cooler-running, longer-lasting sidewalls.

Specifications for Tread Design: WIDE BASE XZL™

Size	Tread	Load Range	Catalog Number	Loaded Radius in.	Overall Diameter in.	Overall Width ‡ in.	Approved Rims width	Min. Dual Spacing ‡ in.	Revs Per Mile	Tread Depth 32nds	Max Speed mph ⁽¹⁾	Single		Dual		
												Max Load	PSI	Max Load	PSI	
445/65R22.5	XZL	L	84103	21.2	46.0	17.6	14.00, 13.00	—	453	26	55*	12300	120	—	—	

Engineered to excel in:

LONG HAUL	REGIONAL	ON/OFF ROAD	URBAN
-----------	----------	-------------	-------

Note: Rim listed first is the measuring rim.
*The 445/65R22.5 XZL LRL is authorized for use at 65mph for up to 100 miles. See Technical Bulletin ES-MATT-97-1 (MWT41096) for further information.
‡ Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
Michelin tires and tubes are subject to a continuous development program. Michelin North America reserves the right to change product specifications at any time without notice or obligations.
⁽¹⁾ Exceeding the lawful speed limit is neither recommended nor endorsed.



An Equal Opportunity Employer ©1998 MNA, MWL 41150



Load & Pressure
XZL(Wide Base)

445/65R22.5 LRL

PSI		75	80	85	90	95	100	105	110	115	120	
lbs per axle	S	17320	18180	18960	19740	20400	21200	22000	22800	23400	24600	
	D											
kg per axle	S	7856	8246	8600	8954	9253	9616	9979	10342	10614	11200	
	D											

